

BENCH



SPECIFICATIONS

Material/Composition: Aluminum and fiber-glass re-enforced polypropylene panels

Available colors: Beige and Grey

Maximal weight rating: 227kg (500lbs)

Needed tools: G2 key for pin, and ½" ratchet socket or wrench

***The hardware of this product is made of stainless steel and brass. If you are installing this product in a salty environment, or if there is a risk of corrosion, replace brass components with stainless steel ones. Don't forget to apply anti-seize grease to the nuts.*

[Youtube instructions](#)

SKU NUMBERS

BENCH BEIGE: C03-000011

BENCH GREY: C03-000012

ASSEMBLY PROCEDURE

- 1-Establish the location of the future BENCH on the dock.
- 2-Remove the two (2) regular CONNECTING PINS located under the bench's future location.
- 3-Insert the 2 CONNECTING PIN W/ MULTI-BASE ADAPTOR that support the legs for the bench. Initiate the screwing process by hand.
- 4-When the pins are properly inserted, proceed by screwing manually using the key for pin as a lever inside the **pre-drilled hole**
- 5-Make sure to securely tighten the CONNECTING PIN W/ MULTI-BASE ADAPTOR until snug.
- 6-You can now assemble the bench parts (the two (2) panels and the two (2) frame units). While assembling the panels, use the aluminum re-enforced one for the seat and the regular one for the backrest. Properly align the mounting holes together while centering the panels on the frame units. We recommend using "long nose" pliers to prevent the bolts from stripping the plastic inserts while screwing the nuts in place.
- 7-Simply insert the bench assembly into the CONNECTING PIN W/ MULTI-BASE ADAPTOR.

