

SWIM LADDER



USEFUL LINKS AND RESOURCES:

[Website](#)

[YouTube](#)

[Box content](#)

SPECIFICATIONS

Material/Composition: High-density polyethylene resin

Available colors: Beige and Grey

Maximal weight rating: 114kg (250lbs)

Needed tools: G2 key for pin, Key for nut, and 9/16" ratchet socket and wrench

***Needed nuts and spacers included.**

****The hardware of this product is made of stainless steel and brass. If you are installing this product in a salty environment, or if there is a risk of corrosion, replace brass components with stainless steel ones. Don't forget to apply anti-seize grease to the nuts.**

SKU NUMBERS

SWIM LADDER BEIGE: C03-000020

SWIM LADDER GREY: C03-000021

ASSEMBLY PROCEDURE

- 1-Pre-assemble the ladder as shown on the manual included in the box.
- 2-Establish the desired location of the ladder.
- 3-Remove the (2x) regular CONNECTING PINS and BOLTS FOR CUBE located where you wish to install the ladder.
- 4-Insert and tighten the (2x) provided connecting pins with threaded rods.
- 5-Insert the two (2) treaded parts of the ladder's up-rights into the chosen tabs. Manually engage the threads of the NUTS.
- 6-Insert the threaded rods of the connecting pins into the uprights' holes and screw the brass nuts and washer firmly.
- 7-Firmly tighten the NUTS with the proper tool.

TIPS

- Make sure to include the (4x) needed SPACERS on the threaded shafts of the (2x) uprights (2 on each side).