


## Adjustable Cradle Pair

### Instructions

Part #: 1006967

Parts List			
ITEM	QTY	PART NUMBER	DESCRIPTION
1	2	1001754	Adjustable Cradle Rubber - EPDM 99260-P
2	2	1004367	Prt Channel 20.5 - Adjustable Cradle
3	2	1005652	Wdmt Cradle Leg 12.0 Adjustable
4	2	1005653	Wdmt Cradle Pocket Adjustable
--	1	1002234	Bolt Bag - Adjustable Cradle
5	4	1002432	Bolt Hex 3/8-16 x 3.0 SS 304
6	8	1001802	Nut Hex Flange 3/8-16 Brass
7	2	1002429	Bolt Hex 3/8-16 x 2.25 SS 304
8	2	1002434	Bolt Hex 3/8-16 x 3.5 SS 304
9	12	1001968	Bolt Carriage 5/16-18 x 1.0 SS 304
10	12	1001807	Nut Hex 5/16-18 Brass



Failure to follow instructions may result in personal injury and may invalidate the applicable warranty.

**Step 1.** Bolt the blue cradle rubber to the cradle channel using six 5/16 x 1 hex bolts and 5/16 hex nuts.

**Step 2.** Bolt cradle leg to cradle channel using one 3/8 x 3-1/2 hex bolt and 3/8 hex nut.

**Step 3.** Slide the adjustable cradle pockets over the rack beam and bolt in place at desired position using two 3/8 x 3 hex bolts and 3/8 hex nuts.

**Step 4.** Insert cradle leg into adjustable cradle pocket and bolt in place at desired height using one 3/8 x 2-1/4 hex bolt and 3/8 hex nut.

**Step 5.** Adjust the cradle channel to the desired angle and tighten bolts securely.

**Note:** The cradle channel is adjustable so the adjustable cradle can run either perpendicular or parallel to the boat. Always tighten the cradle channel so it will not swivel freely.

